

STONE FILL, CULVERT LINING

****From Cabot-Danville FEGC F 028-3(26) C/1**

- xx. DESCRIPTION. This work shall consist of furnishing and placing stone fill inside box culverts to facilitate aquatic organism passage.
- xx. MATERIALS. Stone for Stone Fill, Culvert Lining shall meet the requirements shown in the Plans.
- xx. PLACING. Stone fill shall be placed at the bottom of the concrete box as shown in the Plans. Place the stone such that it does not cause segregation or damage to the concrete box.

Fill in the voids in the stone with a mixture of fines from the existing stream bed material. Fill voids by hand tamping with metal tamping rods, plate compactors, and water pressure with a metal wand to reach between stones.

Once all material has been placed in the stream channel, the Contractor shall slowly wet the stream to minimize the effects of the initial sediment pulse. Every attempt shall be made to minimize the movement of sediment downstream of the site.

- xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Stone Fill, Culvert Lining) to be measured for payment will be the number of cubic meters (cubic yards) installed in the complete and accepted work, measured within the limits shown on the Plans or as directed by the Engineer.
- xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Stone Fill, Culvert Lining) will be paid for at the Contract unit price per cubic meter (cubic yard). Payment will be full compensation for furnishing, transporting, and placing the material specified and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
900.608 Special Provision (Stone Fill, Culvert Lining)	Cubic Meter (Cubic Yard)